

Carburetor Shipping Preparation Checklist

Print this checklist out and use to pack your carburetors

- Remove pod (individual style) air filters from carburetors -- if you want them serviced, they must be individually wrapped and carefully packed in the box, away from the carburetors
- Open all six float bowl drain screws and drain out fuel
- Afterward, lay carbs upside-down in a catch pan for 30 minutes to remove liquid fuel and fumes -- postal authorities will delay and sometimes cancel shipments that have fuel odors
- You may leave the throttle cables attached, but pack carefully to avoid damage to the cables and scratches to the carburetors
- It is best if carburetors are not already disassembled, but if they are to any degree taken apart, make sure that at least the floats are mounted and the float bowls attached, to protect floats
- If there are any loose pieces such as screws or jets or other parts, please put them in a ziplock bag before putting them inside the box -- any newly-purchased parts must be packed carefully
- Don't forget to include the fuel tank petcock (fuel valve) -- wrap it carefully
- The very best box stuffing is stiff paper, with the second best newspaper -- do not use foam "peanuts" or similar kinds of loose packing material -- they don't support heavy objects well
- Use minimum 3" of stuffing all around inside box -- the ideal box is 24" x 10" x 10"
- Put your name, address, phone number below, and put this checklist inside an envelope, put the envelope inside your box, taped to the inside of the upper flap



28532 Casanal
Mission Viejo, CA 92692